

S6 series LED Street light



DESCRIPTION

This series of street lamps are designed for general road lighting, and are suitable for general streets, communities, parks, parks, roads, squares and so on.

FEATURES

- Integrated aluminum die-casting shell, excellent heat dissipation structure, to ensure reliable long life.
- PC optical design, with excellent weather resistance,
 UV linear resistance, aging resistance.
- Excellent sealing structure design, IP65 protection level
- Easy to install, suitable for φ60mm standard lamp pole, SL30S6-SL70S6 suitable for φ45mm lamp pole.

Materials

- Housing:Aluminum
- Lens:PC
- Screw:Stainless steel

Datasheet

110-277VAC

ELECTRICAL

- Input voltage: \sim 110-277 V 50Hz,

- Power Factor: >0.9

- Flash: YES

- Safety Class: CLASS I

- Surge: 1 KV (Differential mode), 2 KV (Common mode)

PERFORMANCE

- Improved efficacy up to 125lm/W
- CRI80 for stander, CRI70 is optional
- IP65,IK06

Operational temperature

-20°C~+40°C, out door


<u> </u>				1		1
SH-SL100S6	110-277VAC	0.47A	100	12500	80	-6500




S6 series LED Street light

Dimension & packaging

						I.
SH	-SL100S6	382*200*42	384*202*47	1	0.88	1.1





Installation Possibilities

